

G600

G600 - Frameless glass wall



CORFLEX

corflex.ca



G601 and G602 series- Frameless glass wall

Give access to your space thanks to Corflex's frameless glass wall. Available in individual assembly (G601) or in pairs (G602), it is now possible to move them manually and easily.

Composed of a single tempered glass of 12mm (1/2"), Corflex's G600 glass wall has no floor track, thus eliminating tripping hazards and the accumulation of debris. The panels are equipped with foot locks and a key lock is also available.

Available in full-height glass, intermediate doors and pivot doors with optional door closer make it easier to access your space. Thanks to their sleek design and the absence of vertical mullions between the panels, Corflex's frameless glass wall maximizes the contribution of natural light to your space.



PROPERTIES

Maximum height per panel

- 3658mm (12') without intermediate door (G601-G602)
- 3048mm (10') with intermediate door (G601)

Maximum width per panel

- 1219mm (4')

Partition weight

- 31,7kg/m² (6,5lbs/ft²)

Type of glass

- Tempered glass 12 mm

Top and bottom sweeps

- Brushes

CHARACTERISTICS

- Anodized aluminum shoes
- Top supported panels
- No floor track
- No vertical trims
- Floor pin on all panels
- Choice of 2 profiles
- Optional panic bar (with pivot door)
- Optional automatic door closet (with pivot door)
- Optional stainless steel shoes cover



G600P Series - Frameless movable glass wall with parallel stacking

The absence of intersections in the track simplifies displacement of the panels. Specifically designed for commercial applications, the G600P series glass wall will be particularly useful for large openings such as storefronts.



PROPERTIES

Maximum height per panel

- 3048mm (10')

Maximum width per panel

- 1219mm (4')

Partition weight

- 31,7kg/m² (6,5lbs/ft²)

Type of glass

- Tempered 12mm glass

Top and bottom sweeps

- Brushes

CHARACTERISTICS

- Anodized aluminum shoes
- Top supported system
- Up to 5 parallel tracks
- No floor track
- No vertical trims
- Floor lock on all panels
- Choice of 2 profiles
- Optional stainless steel shoe cover



G600M series- Motorized operable glass wall

The simple activation of the electric motor allows the linear movement of the partition's interconnected panels. Gradual acceleration and deceleration ensure smooth movement. Easy to adapt, this partition allows you to amalgamate fixed and motorized panels.



PROPERTIES

Maximum height per panel

- 3048mm (10')

Maximum width per panel

- 1219mm (4')

Partition weight

- 31,7kg/m² (6,5lbs/ft²)

Type of glass

- Tempered 12mm glass

Top seals

- Brushes

Bottom seals

- Teflon covered steel guides

CHARACTERISTICS

- Motorized deployment/storage
- Anodized aluminum shoes
- Top supported system
- Floor recessed guide rail
- No vertical trims
- Choice of 2 profiles
- Optional stainless steel shoe cover